



### Product Data Sheet

## 3332-1 | 1/32" BLACK POLYETHYLENE SINGLE COATED FOAM TAPE

1/32" thick black closed cell, cross linked polyethylene foam coated on one side with a high performance acrylic based adhesive with a white kraft liner.

### CONSTRUCTION DIAGRAM



### FEATURES & BENEFITS

- Die cuts easily
- Excellent gasketing material
- Good cushioning qualities
- Great for vibration dampening
- Typical applications: gasketing, gap filling and cushioning

### PROPERTIES

TEST	METHOD	TYPICAL VALUE US	TYPICAL VALUE METRIC
180° Peel	PSTC-101	75 (oz/in)	21 (N/25mm)
Tack	ASTM D2979	800 (oz/in)	222 (N/25mm)
Application Temperature		65 to 120 (°F)	18 to 49 (°C)
Service Temperature		-20 to 212 (°F)	-29 to 100 (°C)

\*\* Tack numbers may not be exact value of tack as foam can tear during tack test. Please contact our sales staff for any assistance.

For maximum adhesion, bonding surfaces should be clean, dry, and free from grease and oils. The firmer the application pressure and the greater the contact area, the stronger the bond. Bond strengths will increase as a function of time as the adhesive continues to wet out the bonding surfaces

**IMPORTANT NOTICE TO PURCHASER:** All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his or her intended use, and the user assumes all risk and liability whatsoever in connection therewith. No representative of ours has authority to waive or change the foregoing provisions, but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to the needs and circumstances prevailing in their business. **ISO 9001 Registered Company.**